

8600 Rocker Switches - Miniature

10A 250Vac Single & Double Pole



Key Features

- ⬡ Miniature rocker switch
- ⬡ Ratings up to 16A, 250Vac
- ⬡ Single & double pole
- ⬡ ON/OFF, C/O, biased and centre off switching
- ⬡ Push on, solder and PCB terminals
- ⬡ Illuminated and non illuminated
- ⬡ Matching indicators
- ⬡ Panel cut out single: 19.3 x 12.9 double: 19.3 x 21.9


Approvals and specifications

- 10(4)A 250Vac T90 (unless noted below)
- UL CSA See ratings below
UL 65°C, file E45221, CSA file LR10990
- 3mm contact gap except where marked μ .


Terminal	Function	Rocker	Body	Body Colour
H 4.8 x 0.8 7.4	Approvals & ratings vary with function 8600 10(4)A 16A 250V, 10A 277V 1/2HP 277V, 1/4HP 125V ON - OFF	V Curved 	B Single pole Panel cut out Bezel 12.9 x 15.0 12.9 x 21.0 15.0 x 21.0 Single Pole dimensions for snap-in fixing Panel thickness 0.75-1.25 1.25-1.99 2.00-3.00 Dim X 19.1/19.2 19.3/19.4 19.7/19.8	B Black
T 3.5 x 0.8 6.4 Solder	8601 6(1)A 16A 250V, 6A 277V ON - OFF (momentary ON)	V Curved (lit) 	B (Double Pole) with terminal barrier Panel cut out Bezel 12.9 x 15.0 12.9 x 21.0 15.0 x 21.0 Double Pole dimensions for snap-in fixing Panel thickness 0.75-1.24 1.25-1.99 2.00-3.00 Dim X 19.1/19.2 19.3/19.4 19.7/19.8	R Red
X 3.7 x 0.85 5.3 PCB 0.85q	8602 10A 6A 277V ON - OFF (momentary OFF)	H Slotted for actuator (8600 and 8610 only) 	BC (Double Pole) w/o terminal barrier Panel cut out Bezel 12.9 x 15.0 12.9 x 21.0 15.0 x 21.0 Double Pole dimensions for snap-in fixing Panel thickness 0.75-1.24 1.25-1.99 2.00-3.00 Dim X 19.1/19.2 19.3/19.4 19.7/19.8	W White
N/A ON - OFF Lit	8650 10(4)A 10A 277V 1/2HP 277V, 1/4HP 125V ON - OFF	F Flat Indicator only (Single pole) 	Cut-outs must be punched in the direction of insertion	
8610 6(1)A 10A 277V 1/2HP 277V, 1/4HP 125V ON - OFF	8651 6(1)A 6A 277V ON - OFF (momentary ON)	8653 10(4)A 6A 277V ON - OFF Lit		
8611 6A 277V ON - OFF (momentary 1 side)	8660 6(1)A 10A 277V 1/2HP 277V, 1/4HP 125V ON - OFF	8660 6A 277V ON - OFF (momentary 1 side)		
8620 μ ON - OFF - ON	8670 μ ON - OFF - ON			
8630 6(1)A UL E63363 CSA LR29381 KEMA-KUER Indicators	N/A			

Dimensions

Single pole



Double pole



Rocker Colour	Lamp Voltage	Legend	Legend Colour	Options
Lit (DP) A Amber C Clear G Green R Red Lit (DP) B Black R Red W White	Blank 2 125V Neon 3 250V Neon 7 12V Filament 8 24V Filament	Blank 076	Blank B Black W White	Finish Matt finish only. Colour Call sales for custom colours. A full range is available for large orders. Legend printing Select from the examples or call sales for custom legend. Lamp voltage Call sales for details of available voltages. Blanking plate A8634FB Dummy unit to fill unused panel holes. Single pole size only. Protective covers L167 for SP L180 for DP Snap on to bodies with V rocker or F lens. This reduces panel thickness by 2.2mm.  Single Pole options Most switches shown can have single pole switching in double pole bodies.

Examples

