



Position	A±0.1	B±0.2	C±0.2	D±0.2		E±0.2
				Male	Female	
9P	10.16	30.80	24.99	17.90	16.33	19.00
15P	17.78	39.14	33.32	26.50	24.66	27.34
25P	30.48	53.04	47.04	40.00	38.38	41.24
37P	45.72	69.32	63.50	56.50	54.84	57.52

NOTES:

- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 30m Ω ? Max.INITIAL.
 - DIELECTRIC WITHSTANDING VOLTAGE:500V AC(rms) FOR 1 MINUTE.
 - INSULATION RESISTANCE:1000M Ω ? Min.
- MECHANICAL CHARACTERISTICS:
 - DURABILITY: 300 CYCLES.
- ENVIRONMENT CHARACTERISTICS:
 - TEMPERATURE RANGE: -40°C~+105°C.

4. PRODUCT NUMBER CODE:

- DS1036 - XX X X X X X X - YT
- SCREW TYPE
 - X:W/O SCREW
 - 1:CC TYPE
 - 2:CS TYPE
 - RIVET TYPE
 - P:W/ THREAD(UNC #4-40)
 - N:W/O THREAD(FOR W/O SCREW ONLY)
 - CONTACT PLATING
 - 2: GOLD+NICKEL
 - HOUSING COLOR
 - U:BLUE
 - B:BLACK
 - STRAIN RELIEF
 - P:W/
 - N:W/O
 - CONNECTOR TYPE
 - M:MALE
 - F:FEMALE
 - No.OF CONTACTS
 - 09:9pos 15:15pos
 - 25:25pos 37:37pos

