

https://www.engineertools-jp.com/








## HEAD OFFICE .

8-9, HIGASHI IMAZATO 2-CHOME, HIGASHINARIKU, OSAKA 537-0011, JAPAN TEL:06-6974-0028 FAX:06-6974-5661






## **Screw Removal Pliers Series**




#### Socket Screw Extractor Series



## **Phillips Screw Extractor Series**



#### **Rust Remover**





# Screw Removal Pliers Series



Ideal for board work such as SSD and maintenance of home-built PCs

PZ-60

For deep places

#### **Black Finish**

Reduces light reflection and rust Black oxide coated

Tough model for outdoor uses



#### Maintenance

**Electrical Work** 

Specializes in electrical work

such as cutting wires and tightening cable ties

various tasks



Maintenance and demolition PZ-59 at work sites and other

PZ-54

Switchable fulcrum

PZ-75 NEW



Strongest and most powerful!

Shears cables in a snap Two blade types

Easy cutting of VA wires and welding

30% increased cutting power



















## **Plumbing Work**

Necessary functions added for plumbing and piping works

PZ-78

Ideal for working in secluded places, and also for vinyl coated pipe works



Φ3~9.5

## Auto Mechanic

The vice function allows the screw to be locked strongly

#### PZ-67

No need to adjust!

More big, more powerful!

Small type for easy handling

and large type that is easy to apply force

PZ-68 NEW

PZ-64 · 65

For deep places

PZ-66



Φ3~9.5

Φ3~9.5



Φ3~9.5



Φ3~5.5









· Grip super-thin screw heads tightly!

· Tapered and slender head is ideal for working in a confined area

















Patented











Cutting Capacity (mm) Stainless Wire







Comes with a pliers mask for neat storage (PZM-77)



#### Your "Go-To" tool to tackle many daily challenges!






















· Spring loaded for fatigue-free work









#### **Related Products**






Dome head

#### Screw Eater (PZ-22)














- · Just grip and turn!! High leverage structure makes it easy to grip
- · Inter-meshed Side Teeth -- Enough force to grip ultra-thin plates as tightly as thick materials when the jaws are closed









## Screw Removal Pliers (PZ-55)

· The basic Screw Removal Pliers: powerful and simple!







Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size ( mm )	Cutting capacity (mm)	Weight (g)	Material
PZ-77	W182xH50xD15			Copper Wire Φ4.0 Steel Wire Φ3.2	183	
PZ-77P	W182xH50xD15		Ф3~9.5		183	Body:Carbon Steel
PZ-58	W160xH54xD15	60±2		Copper Wire Φ3.2 Steel Wire Φ2.6	130	Handles:TPR
PZ-22	W175xH52xD15			1-	165	(Only PZ-55:PVC)
PZ-55	W150xH53xD11	56±2	Ф3~8	-	125	
PZM-77	*	-	=	-	~	
PZM-77P	-	-		=	-	TPR
PZM-58	-	-		-	i <del>t</del>	

# **Electronic Work**

#### Screw Removal Pliers m2 (PZ-57)



#### Convenient for working on electronic devices Small-sized 120mm body with ESD-safe handles

- · Ideal for removing small stripped or special screws
- · ESD-Safe TPR handles
- · Grip end with strap hole
- · Used for laptops, mother boards, prototype electronics, mobile phones, game consoles, RC toys, drones, character figures and other electronic appliances








#### Screw Removal Pliers Z (PZ-60)



Dome head







#### Alligator-like tough gripping needle nose with screw removing jaws

- · Long nose pliers with non-slip gripping inter-meshed side teeth
- · Screw removal with vertical serrations at the tips just grip & turn!!
- · Durable comfort grips made of TPR
- · Side cutter for copper wires















## **Black Finish**

#### Screw Removal Pliers JS(PZ-32)













#### Multi-purpose extraction tool for stubborn fasteners... Black finish!

- · Vertical serrations grip the screw head without slipping
- · Inter-meshed side teeth make it possible to hold very thin boards firmly
- · Black oxide coating to increase rust-resistance!



#### **Related Products**





Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size ( mm )	Cutting capacity (mm)	Weight (g)	Material
PZ-57	W120xH52xD11	56±2	Φ2~3.5	_	100	5 1 6 1 6 1
PZ-60	W193xH57xD15		Φ2~5.5	Copper Wire Φ3.2	180	Body:Carbon Steel
PZ-32	W160xH55xD16	60±2	Φ3~9.5	Steel Wire Φ2.6	125	Handles:TPR
PZM-30	1-11	-	-	-	-	TPR


# Maintenance

#### Screw Removal Pliers RX (PZ-59)











#### 8-inches heavy-duty screw extracting tool, the multi-purpose gripping pliers The patented vertically-serrated jaws can bite a damaged, broken or rusted screw head with no slip!



- · Ideal for professionals, auto mechanics, builders, etc
- · Inter-meshed side teeth make it possible to hold very thin boards firmly





#### Screw Removal Pliers CP (PZ-54)



Dome head





#### Slip-joint Screw Removal Pliers: 2-way opening jaws!

- · Unique and vertically-serrated jaws grip a stripped screw head securely without slipping
- · Much faster than a fluted screw extractor and simpler than vise grip pliers
- · Side cutter for steel wires. (dia. 2mm max.)
- · Side jaws ideal for holding a round pipe, hexagonal nut, etc













Grip super-thin screw head tightly!





Item No.	Size	Tip hardness (HRC)	Applicable screw head size ( mm )	Cutting capacity	Weight (8)	Material
PZ-59	W204xH53xD19	60±2	Ф3~12	Copper Wire Φ3.5 Steel Wire Φ3.2	295	Body:Carbon Steel Handles:TPR
PZ-54	W175xH48xD14	00±2	Ф3~9.5	Steel Wire Φ2.0	155	Body:Carbon Steel Handles:PVC

# **Electrical Work**

### Screw Removal Pliers VAX (PZ-75) NEW

- · Grip super-thin screw heads tightly!
- · Cuts PVC insulated 3-core cables easily with one hand
- · A must for electricians!




















Vertical serrations for screw removal

#### Screw Removal Pliers VA (PZ-79)

· Crimper for bare terminals (AWG16~12)

· Cross-hatched jaws to hold thin plates, cable ties and other parts tightly without slipping







Cross-hatch

· Unique screw removal jaws must for electricians

Screw Removal Pliers EL (PZ-78)





Dome head



Dome head

























Strap hole

Crimper for

bare terminals 1.25~3.5mm<sup>2</sup>

Applicable screw head size ( mm ) Cutting capacity (mm) Tip hardness Blade length Weight Material Size Item No. ( mm ) NEW PZ-75 W205×H53×D14 Ф3~9.5 Steel Wire Φ2.5 Body:Carbon Steel 20 60±2 W215×H52×D27 VVF2.6x3C Handles:TPR Φ3~12 (Only PZ-79:PVC) 350 PZ-78 W225×H54×D27 Steel Wire Φ3.2 21

# **Plumbing Work**

#### Screw Removal Pliers WP-3 (PZ-82) NEW

- · Unique screw removal jaws must for plumbers & mechanics
- · 245mm long body with high leverage and wide opening jaws (max. 50mm)
- · Quick adjustment of opening jaws

Screw head size Φ3~9.5 mm

- · Holds round bars, square bars, hex. nuts, sheet metals, etc.
- · Vertical serrations for removing stripped or rusty screws








Dome head RoHS2

Pipe Φ5~50mm Hex. nut 5~47mm

# **Quick Adjust Grooved Joint**



Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size ( mm )	Max. opening (mm)	Weight	Material
NEW PZ-82	W245×H57×D27	60±2	Ф3~9.5	50	350	Body:Carbon Steel Handles:PVC



## Self-locking function

No need to adjust the jaws opening, just clamp it to lock!





## Screw Removal Pliers VP-4 (PZ-67)





#### Screw Removal Pliers VP-5 (PZ-68) NEW





















# Clamping force adjustment





Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size ( mm )	Weight (g)	Material
PZ-67	W175×H52×D18	57±3	±2.0F	265	Dadw.Chuana Malubdaa.us
NEW PZ-68	W220×H64×D20	5/±3	Ф3~9.5	550	Body:Chrome Molybdenum

#### Screw Removal Pliers VP-1 · 2 (PZ-64 · 65)

#### Hold the screw head and lock it up to twist!!

· Quick release mechanism: just open the handles to unlock











Can be retightened with a hex key wrench (3mm)









Can be retightened with a hex key wrench (4mm)




· Slender nose type















Can be retightened with a hex key wrench (3mm)

10









Quick release: just pull the handles with both hands

Item No.	Size (mm)	Tip hardness (HRC)	Applicable screw head size ( mm )	Cutting capacity (mm)	Weight (g)	Material
PZ-64	W150×H55×D18		Ф3~9.5	Copper Wire Φ1.6	205	
PZ-65	W190×H70×D25	57±3		Copper Wire Φ2.3	400	Body:Chrome Molybdenum Handles:TPR
PZ-66	W150×H55×D18			-	210	Hallules, IFN

#### Socket Screw Extractor Series



Remove stripped hex socket screws without hammering!








#### How to Choose

# Short Type










For screws in deep holes







## Middle Type

[DBZ-410~450]



65mm Bits









## Long Type

[DBZ-62~65]









#### Socket Type

[DWZ-05~10]



## Square drive type allen bolt extractors





#### Select by across flats size

O Acro	ss Flats Size	H0.89	H1.5	H2	H2.5	нз	H4	Н5	Н6	Н8	H10
Short		310	315	320	325	330	340	350	¥	*:	-
Middle	DBZ-	410	415	420	425	430	440	450	-	H	3
Long		-	*	62	63	63	64	65	-	- 5	-
Socket	DWZ-	9	-	7-	- 3	-	14	05	06	08	10



#### Select by screw size

Screw size	Hex socket screw	Button	Flat head	Hex socket set screw	
M1.0	DBZ-310 / 410			E	
M1.6	DBZ-315 / 415	-	-	-	
M2.0	DBZ-313 / 415	(A)	=	DBZ-310 / 410	
M2.5	DBZ-320 / 420 / 62	DBZ-315 / 415	DBZ-315 / 415		
M3.0	DBZ-325 / 425 / 63	DBZ-320 / 420 / 62	DBZ-320 / 420 / 62	DBZ-315 / 415	
M4.0	DBZ-330 / 430 / 63	DBZ-325 / 425 / 63	DBZ-325 / 425 / 63	DBZ-320 / 420 / 62	
M5.0	DBZ-340 / 440 / 64	DBZ-330 / 430 / 63	DBZ-330 / 430 / 63	DBZ-325 / 425	
M6.0	DBZ-350 / 450 / 65 , DWZ-05	DBZ-340 / 440 / 64	DBZ-340 / 440 / 64	DBZ-330 / 430	
M8.0	DWZ-06	DBZ-350 / 450 / 65 , DWZ-05	DBZ-350 / 450 / 65 , DWZ-05	DBZ-340 / 440	
M10	DWZ-08	DWZ-06	DWZ-06	DBZ-350 / 450 / 65 , DWZ-05	
M12	DWZ-10	DWZ-08	DWZ-08	DWZ-06	
M14	-	-	DW7.40	=	
M16	-	DWZ-10	DWZ-10	DWZ-08	
M20	-	-	-	DWZ-10	


# Application to Torx, Phillips, etc. Phillips





# Select the appropriate size for the pilot hole





Drill a pilot hole in the center of screw head.

Apply the tip of the extractor and turn it counterclockwise.

	Remove stripped hex socket screws without hammering					Application to Phillips,Torx			
Item No.	Across	Can hall	Hexago	n socket	Hex socket	Diameter	BE III	Torx	Max. limit of size *1
	flats 🙂	Cap bolt	Button	Flat head	set screw	(mm)	Phillips	TOTA	
DBZ-310 / 410	H0.89	M1		*	M2	Ф 1.0	M1.6	T3,T4	M2
DBZ-315 / 415	H1.5	M1.6,M2	M2.5	M2.5	M3	Ф 1.5	M2	T5,T6	M2.6
DBZ-320 / 420 / 62	H2	M2.5	M3	M3	M4	Φ 2.0	M2.6	T7, T8	МЗ
DBZ-325 / 425 / 63	H2.5	M3	M4	M4	M5 *2	Φ 2.5	М3	T10	M4
DBZ-330 / 430 / 63	H3	M4	M5	M5	M6 *2	Ф 3.0	M4 *2	T15 *2	M5
DBZ-340 / 440 / 64	H4	M5	M6	M6	M8 *2	Φ 4.0	M5	T20,T25	M6
DBZ-350 / 450 / 65 , DWZ-05	H5	M6	M8	M8	M10	Ф 5.0	M6	T27,T30	M8
DWZ-06	H6	M8	M10	M10	M12	Φ 6.0	M8	T40	M10
DWZ-08	H8	M10	M12	M12	M16	Φ 8.0	M10	T45, T50	M12
DWZ-10	H10	M12	M16	M14,M16	M20	Ф10.0	2	T55	M16

- \*1 Use of screws larger than the maximum size limit may result in damage. Excluding set screws.
- \*2 Excluding DBZ-63, DBZ-64



Compatible screw


For more information about tool selection and actual working methods, please check here.

## **▼** Watch the case study blog!















#### Socket Screw Extractor - Short Bits - (DBZ-310~350)

 Super-short (18mm) Socket screw extractors, ideal for working in narrow spaces.

#### Short Type





DBZ-350














Size / Compatible screw

Item No.	Across flats(mm)	Cap bolt	Hex socket button& flat head	# 2 Hex socket set screw
DBZ-310	0.89 *1	M1	-	M2
DBZ-315	1.5	M1.6 / M2	M2.5	M3
DBZ-320	2	M 2.5	M3	M4
DBZ-325	2.5	M3	M4	M5
DBZ-330	3	M4	M5	M6
DBZ-340	4	M5	M6	M8
DBZ-350	5	M6	M8	M10



Daniel No.	Size	(mm)	Weight
Item No.	Α	В	(g)
DBZ-310	5	Ø1.4	2.8
DBZ-315	6	Ø2.2	2.9
DBZ-320	6	Ø3.0	3.1
DBZ-325	6	Ø3.9	3.4
DBZ-330	6	Ø4.6	3.6
DBZ-340	6	Ø5.5	4.0
DBZ-350	-	-	4.3

Socket Extractor Short Set (DBZ-301)

#### NEW



[Contents] DBZ-310 DBZ-315 DBZ-320 DBZ-325 DBZ-330 DBZ-340

DBZ-350

#### Socket Extractor Short Set (DBZ-302)

#### NEW



[Contents] DBZ-310 DBZ-315 DBZ-320 DBZ-325

## Socket Extractor Short Set (DBZ-303)

[Contents] DBZ-325 DBZ-330 DBZ-340 DBZ-350

## Mini Offset Ratchet with Socket Extractor Set (DZ-273)



#### Mini Offset Ratchet with Socket Extractor Set (DZ-275)



[Contents] DR-27 DBZ-302

## Mini Offset Ratchet with Socket Extractor Set (DZ-276)



[Contents] DR-27 DBZ-303

(6.35) (PoHS2

#### Mini Offset Ratchet (DR-27)

#### Super-thin head for narrow spaces

·Standard bits: (+) #2 & (-) 6mm ·Ouick ratchet dial



103 mm



# Middle Series

#### Socket Screw Extractor - Middle Bits - (DBZ-410~450)

- · 65mm long Socket Screw Extractors
- · Ideal for working in limited spaces

#### Middle Type








#### Size / Compatible screw

Item No.	Across flats(mm)	Cap bolt	Hex socket button& flat Head	* 2 Hex socket set screw
DBZ-410	0.89 *1	M1		M2
DBZ-415	1.5	M1.6 / M2	M2.5	M3
DBZ-420	2	M 2.5	M3	M4
DBZ-425	2.5	M3	M4	M5
DBZ-430	3	M4	M5	M6
DBZ-440	4	M5	M6	M8
DBZ-450	5	M6	M8	M10



	Size	Weight	
Item No.	Α	В	(g)
DBZ-410	10	Ø1.4	11.5
DBZ-415	15	Ø2.2	11.2
DBZ-420	15	Ø3.0	11.4
DBZ-425	_	Ø3.9	12.6
DBZ-430	-	Ø4.6	13.5
DBZ-440	<del></del>	Ø5.5	14.6
DBZ-450	-	-	16.2

#### Socket Extractor Middle Set (DBZ-401)

NEW



[Contents] DBZ-410 DBZ-415 DBZ-420 DBZ-425 DBZ-430 DBZ-440 DBZ-450

#### Socket Extractor Middle Set (DBZ-402)



[Contents] DBZ-410 DBZ-415 DBZ-420 DBZ-425

#### Socket Extractor Middle Set (DBZ-403)

NEW



[Contents] DBZ-425 DBZ-430 DBZ-440 DBZ-450

#### Socket Screw Extractor Set with Mini Handle (DZ-84)



[Contents] DZ-80 DBZ-401

#### Socket Screw Extractor Set with Mini Handle (DZ-85)



[Contents] DZ-80 DBZ-402

#### Socket Screw Extractor Set with Mini Handle (DZ-86)





[Contents] DZ-80 DBZ-403

#### Mini Handle (DZ-80) Handle only NEW

Compact body with excellent portability and operability Rotary head for precision work









[Actual size]

# Long Series

#### Socket Screw Extractor - Long Bits - (DBZ-62~65)



4-in-1 Socket Screw

Extractor Set (DBZ-20)



65mm long Socket Screw Extractors



#### Size / Compatible screw

	01	9	99	8		item No.	Size (mm)	Weight (g)
Item No.	Across	Cap	Hex socket	*	25	DBZ-62		25
item No.	flats(mm)	bolt	flat head	Hex socket set screw		DBZ-63		27
D8Z-62	2	M2.5	M3	M4	105	DBZ-64	105	27
D8Z-63	2.5 ~ 3	M3 / M4	M4 / M5		k 103	DBZ-65		27
DBZ-64	4	M5	M6			DBZ-20		125
DBZ-65	5	M6	M8	M10				

(\*) Do not use on stuck hex socket set screws.





#### Go-through Screwdriver (DZ-70) Handle only



171

-

[Contents] DZ-70

**DBZ-20** 

- · Ergonomically designed comfort handle accepts 6.35mm driver bit (Bit length over 50mm recommended)
- · The handle is narrow in the middle to place fingers here for safety, and useful for quick tightening







# Square Drive Series

#### Socket Screw Extractor -Square Drive type- (DWZ-05~10) NEW

- Removing hexagon socket (Allen) screws and hex. socket set screws that are broken by an Allen key. For hex. size 5-10mm (AF)
- ·Works with your own socket wrench handle (9.5mm sq. drive)






















[Contents] DWZ-05, DWZ-06, DWZ-08, DWZ-10


		0	99	-
Item No.	Across flats(mm)	Cap bolt	Hex socket button& flat head	Hex socket set screw
DWZ-05	5	M6	M8	M10
DWZ-06	6	MB	M10	M12
DWZ-08	8	M10	M12	M16
DW7.40	40	MAG	884478846	MAZO



And the second second second		11000	
Item No.	A	В	(g)
DWZ-05	12.3	8	24
DWZ-06	13	9.6	26
DWZ-08	13.4	12.5	29
DWZ-10	14	15	33
DWZ-302	121		120

# Combination of Socket Screw Extractors

#### Related products



Compatible tools	Mini Offset Ratchet (DR-27)  Mini Ratchet Wrench (DR-37)	Extendable Ratchet Handle (DR-47) + Bit Adapter (DR-35)	Extension Bit Holder (DR-28)  Universal Joint (DR-26)	Mini Handle (DZ-80)  Go-Through Screwdriver (DZ-70)	Extension Bit Holder (DR-22 · 23 · 24)  Universal Joint (DR-25)
Short Type (DBZ-310~350)	0	0	0	×	×
Middle Type (DBZ-410~450) ————————————————————————————————————	Δ *	Δ *	Δ *	0	0
Long Type (DBZ-62~65)	Δ *	Δ **	Δ *	0	0

※△ It can be installed, but the bit may be damaged. Do not use for screws larger than M6.





## Remove the stripped countersunk screw without hitting it with a hammer







Press & Twist type

DBZ-58

of the blade tip


#### Extractor Bit for "slightly damaged phillips screws" (DBZ-51-57-58)

- ·Elaborately crafted blades catch the stripped Phillips screw
- ·DBZ-51 for Phillips No.2 screw requires no hammer Simply press down on the screw & twist it out!!
- Shank size: Hex. 6.35mm

DBZ-51









DBZ-57

Item No.	Screw size	Weight (g)
DBZ-51	No.2 (M3~5)	24
DBZ-57	No.1 (M2~3)	25
DBZ-58	No.0 (M1.4~2)	25

Strike & Turn type

## Extractor Bit for "heavily damaged phillips screws" (DBZ-52)


Strike the end with a hammer to stick the blade into the recess












#### Item No. Screw size DBZ-52 No.2 (M3~5) 27


#### Rapid removal! Designed for heavily-damaged hexagon socket screws

Strike & Turn type









Item No.	Screw size	Weight (g)
DBZ-53	2.5~3mm	
DBZ-54	4mm	26
DBZ-56	5mm	

#### 4-in-1 Rapid Screw Extractor Set (DBZ-22)



Bit holder included



Item No.	Case size (mm)	Weight (g)
DBZ-22	H165xW75xD10	125

#### Go-Through Screwdriver (DZ-76)



[Contents]

Go-Through Screwdriver 01 (DZ-71)













[Contents] DZ-70 DBZ-51








		Size (mr	n)		I Marieba
Item No.	Shaft length (when inserted)	Shaft across flats	O.A. length	Handle diam.	Weight (g)
DZ-76	73	6.35	194	38	250

#### 4-in-1 Rapid Screw Extractor Set (DBZ-21)



[Contents] DBZ-57 DBZ-51 DBZ-52 DBZ-53



Item No.	Case size (mm)	Weigh (g)
DBZ-21	H165xW75xD10	125

#### Rapid Screw Extractor + Grip Set (DBZ-60G·50G)

The unique extracting tool, especially designed for removing damaged countersunk screws!

- ·No power supply or drilling required
- · 2 bits, more possibilities
- ·High-torque handle grip ·Shock-absorbable rubber sleeve included





	Item No.	Weight (g)	Material
	DBZ-60G	131	■Bit:Carbon Steel ■Rubber:TPR ■Grip:ABS、PA
Grip only	DBZ-50G	83	■Grip:ABS、PA

18

RoHSZ

# Screw Removal Tool Kit By combining these, you can deal with various screw troubles







## **Socket Screw Extractor Set**

Works with 2~5mm (Across flats) stripped hex socket screws






[Contents]


Item No.	Hex. size (across flats)
DBZ-62	2 mm
DBZ-63	2.5 ~ 3 mm
DBZ-64	4 mm
DBZ-65	5 mm







Works with stripped Phillips screws (No.0, No.1 & No.2 sizes)





	1
	U G
A	Press
4000000	& Twist
Philips	Twist

		TWIST	Sci	rew
ifications		O Phi	0	
		Slightly Damaged	Heavily Damaged	Hex socket screw
	DBZ-21	No.2 , No.1	No.2	Across flats 2.5~3 mm
	DBZ-22	No.2 , No.1 , No.0	No.2	-

## Go-through Screwdriver

Ergonomic design for powerful torque









transmitted well to the tip



**Extension Bit Holder** 

Bit holders can also be used with an impact driver

DR-24





Can be used with a

working in a confined area

## Screwdriver Magnetizer

2 pcs. in a set Available in 3 colors

DR-19

DR-19P

DR-19Y




retrieve screws

Magnetized bit can Holds even a stepped bit or torsion bit flexibly

Universal Joint

DR-25





Slide the sleeve forward to swing the tip up to 15 degrees

#### Screw Extractor Tool Kit (DXZ-03~09)

If you're having trouble, start here! By combining these, you can deal various screw troubles.









7-in-1 set (DXZ-07)





Screw Removal Pliers (PZ-77)

8-in-1 set (DXZ-08)










Rust Remover (ZC-28E) Screws rusted and stuck? Try our Rust Remover to remove the rust off screws within seconds!

 $\triangle$  Do not reuse mechanical parts such as springs, chains, and bolts that are subject to strong forces, even after rust removal.







Auto Locking Pliers (PZ-67)

#### CONTENTS



NEW





















	Conten	ts									
Item No.	DZ-70	DBZ-20	DBZ-21	DBZ-22	DR-19	DR-23	DR-25	PZ-67	PZ-77	ZC-28E	KSE-35
DXZ-03	0	0	0								0
DXZ-04	0	0		0							0
DXZ-05	0	0	0		0	0	0				0
DXZ-06	0	0		0	0	0	0				0
DXZ-07	0	0		0	0	0	0		0		0
DXZ-08	0	0		0	0	0	0		0	0	0
DXZ-09	0	0		0	0	0	0	0			0

#### PDS-01

Screw Removal Pliers GT with Mask + Rapid Screw Extractor with 5 bits in a compact heavy duty case



#### Contents

PZ-58	Screw Removal Pliers GT	DBZ-52	Phillips no. 2 (Strike & Turn type bit)
PZM-58	Mask for PZ-58	DBZ-53	Hex socket screw (Across flats: 2.5-3.0mm)
DBZ-50B	Handle Grip for DBZ (Black)	DBZ-54	Hex socket screw (Across flats: 4.0mm)
DBZ-51	Philips no. 2 (Press & Twist type bit)	DBZ-56	Hex socket screw (Across flats: 5.0mm)
			Bit holder

#### PDS-02

Screw Removal Pliers + Phillips Screw Extractor + Hex. Socket Screw Extractor bits in a compact heavy-duty case



Content	S	
PZ-58	Screw Removal Pliers GT	DBZ
PZ-59	Screw Removal Pliers RX	DBZ
PZ-60	Screw Removal Pliers Z	DB2
DBZ-50B	Handle Grip for DBZ (Black)	DB2
DBZ-51	Phillips no. 2 (Press & Twist type bit)	



Z-56 Hex socket screw (Across flats: 5.0mm)



Engineere

# PDS-03

Screw Removal Pliers PZ-33 with Mask cap + Rapid Screw Extractors and Socket Screw Extractors in a compact heavy-dutycase



Content	5		
PZ-33	Screw Removal Pliers DF	DBZ-62	Hex socket screw extractor (2.0mm)
PZM-30	Mask for PZ-33	DBZ-63	Hex socket screw extractor (2.5 - 3.0mm)
DBZ-50R	Handle Grip for DBZ (Red)	DBZ-64	Hex socket screw extractor (4.0mm)
DBZ-51	Phillips no. 2 (Press & Twist type bit)	DBZ-65	Hex socket screw extractor (5.0mm)
			Bit holder

## Rapid Screw Extractor Set(DBZ-01)

Rapid Screw Extractors + Hexagon Socket Screw Extractor of 10 bits in a compact heavy duty case




#### Contents

DBZ-50B	Handle Grip for DBZ (Black)	DBZ-52	1
DBZ-57	Philips no. 1 (Press & Twist type bit)	DBZ-53	1
DBZ-51	Phillips no. 2 (Press & Twist type bit)	DBZ-54	
DBZ-63	Hex socket screw extractor (2.5 - 3.0mm)	DBZ-56	l
DBZ-64	Hex socket screw extractor (4.0mm)	DR-94	I
DBZ-65	Hex socket screw extractor (5.0mm)		l.

Philips no. 2 (Strike & Turn type bit) Hex socket screw (Across flats: 2.5-3.0mm) Hex socket screw (Across flats: 4.0mm) Hex socket screw (Across flats: 5.0mm) Double-headed screwdriver bit (+ #2 / - 6mm)







· Can fit stepped bits or torsion bits flexibly

4mm Round shaft




DR-19 (Green)

Magnetized bit can retrieve screws!







Item No.	Qty.	Shaft size (mm)			Weight (g/pc.)
DR-19 DR-19P DR-19Y	2pcs.	4~6.35	24	13	6.6

#### Mini Screwdriver Magnetizer (DR-29) NEW

6.35mm Hex. shaft











(Yellow)

The grooved housing holds the screw head securely. Common to DR-19,29

Item No.	Qty.	Shaft size (mm)	0.00	10.0303(10.0)	Weight (g/pc.)
DR-29	3pcs.	4~6.35	16.2	13	4

## Micro Screwdriver Magnetizer (DR-39) NEW



length width (g/pc.)





#### Extension Bit Holder (DR-22-23-24)


#### Durable construction works with Go-through screwdrivers by hammering

· Can also be used with an impact driver (except for DR-28)

· Slim head ideal for working in a confined area









Item No.	Size (mm) A	Weight (g)
DR-22	100	40
DR-23	150	52
DR-24	190	60


#### Universal Joint (DR-25)

- · For screws in the corner or near the walls.
- · Unique tip structure prevents bit from coming off.









- 1) Do not use the Universal Joint in swing mode when it is attached to a power tool.
- 2) Use the low speed mode only.
  3) Make sure that the grooved shank is compatible with your power tool.
  4) The joint part heats up during the continuous use. Please work while cooling it with lubricating oil.







#### Extension Bit Holder (DR-28)

- For Short Bit (DBZ-310~350 Extractors attachable)
- Slim head ideal for working in a confined area








Thomas Aller	SIZE	weign
Item No.	(mm)	(g)
DR-28	100	35

#### Universal Joint (DR-26)

· The built-in magnet allows mounting of short bits without ball grooves.





Item No.	Size (mm)	Weight (g)
DR-26	100	53