

# BC546B, BC547A, B, C, BC548B, C

## Amplifier Transistors

### NPN Silicon

#### Features

- Pb-Free Packages are Available\*

#### MAXIMUM RATINGS

| Rating   | Symbol         | Value          | Unit                       |
|--|----------------|----------------|----------------------------|
| Collector - Emitter Voltage<br>BC546<br>BC547<br>BC548                                 | $V_{CE0}$      | 65<br>45<br>30 | Vdc                        |
| Collector - Base Voltage<br>BC546<br>BC547<br>BC548                                    | $V_{CB0}$      | 80<br>50<br>30 | Vdc                        |
| Emitter - Base Voltage   | $V_{EB0}$      | 6.0            | Vdc                        |
| Collector Current - Continuous   | $I_C$          | 100            | mAdc                       |
| Total Device Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 625<br>5.0     | mW<br>mW/ $^\circ\text{C}$ |
| Total Device Dissipation @ $T_C = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$          | 1.5<br>12      | W<br>mW/ $^\circ\text{C}$  |
| Operating and Storage Junction<br>Temperature Range                                    | $T_J, T_{stg}$ | -55 to +150    | $^\circ\text{C}$           |

#### THERMAL CHARACTERISTICS



| Characteristic                             | Symbol          | Max  | Unit                      |
|--|-----------------|------|---------------------------|
| Thermal Resistance,<br>Junction-to-Ambient | $R_{\theta JA}$ | 200  | $^\circ\text{C}/\text{W}$ |
| Thermal Resistance,<br>Junction-to-Case    | $R_{\theta JC}$ | 83.3 | $^\circ\text{C}/\text{W}$ |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.




<http://onsemi.com>



TO-92  
CASE 29  
STYLE 17

#### MARKING DIAGRAM



BC54x = Device Code  
x = 6, 7, or 8  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

#### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

# BC546B, BC547A, B, C, BC548B, C

## ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| Characteristic  |   | Symbol        | Min  | Typ   | Max  | Unit   |   |
|---|---|---------------|--|---|--|--|---|
| <b>OFF CHARACTERISTICS</b>  |   |               |  |   |  |  |   |
| Collector - Emitter Breakdown Voltage<br>( $I_C = 1.0\text{ mA}$ , $I_B = 0$ )  | BC546<br>BC547<br>BC548   | $V_{(BR)CEO}$ | 65<br>45<br>30   | -<br>-<br>-   | -<br>-<br>-  | V  |   |
| Collector - Base Breakdown Voltage<br>( $I_C = 100\ \mu\text{A}$ )  | BC546<br>BC547<br>BC548   | $V_{(BR)CBO}$ | 80<br>50<br>30   | -<br>-<br>-   | -<br>-<br>-  | V  |   |
| Emitter - Base Breakdown Voltage<br>( $I_E = 10\ \mu\text{A}$ , $I_C = 0$ )   | BC546<br>BC547<br>BC548   | $V_{(BR)EBO}$ | 6.0<br>6.0<br>6.0  | -<br>-<br>-   | -<br>-<br>-  | V  |   |
| Collector Cutoff Current<br>( $V_{CE} = 70\text{ V}$ , $V_{BE} = 0$ )<br>( $V_{CE} = 50\text{ V}$ , $V_{BE} = 0$ )<br>( $V_{CE} = 35\text{ V}$ , $V_{BE} = 0$ )<br>( $V_{CE} = 30\text{ V}$ , $T_A = 125^\circ\text{C}$ ) | BC546<br>BC547<br>BC548<br>BC546/547/548  | $I_{CES}$     | -<br>-<br>-<br>-   | 0.2<br>0.2<br>0.2<br>-  | 15<br>15<br>15<br>4.0  | nA<br><br><br>$\mu\text{A}$                                      |   |
| <b>ON CHARACTERISTICS</b>   |   |               |  |   |  |  |   |
| DC Current Gain<br>( $I_C = 10\ \mu\text{A}$ , $V_{CE} = 5.0\text{ V}$ )<br><br>( $I_C = 2.0\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ )<br><br>( $I_C = 100\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ )                            | BC547A<br>BC546B/547B/548B<br>BC548C<br><br>BC546<br>BC547<br>BC548<br>BC547A<br>BC546B/547B/548B<br>BC547C/BC548C<br><br>BC547A/548A<br>BC546B/547B/548B<br>BC548C | $h_{FE}$      | -<br>-<br>-<br><br>110<br>110<br>110<br>110<br>200<br>420<br><br>-<br>-<br>- | 90<br>150<br>270<br><br>-<br>-<br>-<br>180<br>290<br>520<br><br>120<br>180<br>300 | -<br>-<br>-<br><br>450<br>800<br>800<br>220<br>450<br>800<br><br>-<br>-<br>- | -<br>-<br>-<br><br>-<br>-<br>-<br>-<br>-<br>-<br><br>-<br>-<br>- | - |
| Collector - Emitter Saturation Voltage<br>( $I_C = 10\text{ mA}$ , $I_B = 0.5\text{ mA}$ )<br>( $I_C = 100\text{ mA}$ , $I_B = 5.0\text{ mA}$ )<br>( $I_C = 10\text{ mA}$ , $I_B = \text{See Note 1}$ )                   |   | $V_{CE(sat)}$ | -<br>-<br>-  | 0.09<br>0.2<br>0.3  | 0.25<br>0.6<br>0.6   | V  |   |
| Base - Emitter Saturation Voltage<br>( $I_C = 10\text{ mA}$ , $I_B = 0.5\text{ mA}$ )   |   | $V_{BE(sat)}$ | -  | 0.7   | -  | V  |   |
| Base - Emitter On Voltage<br>( $I_C = 2.0\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ )<br>( $I_C = 10\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ )  |   | $V_{BE(on)}$  | 0.55<br>-  | -<br>-  | 0.7<br>0.77  | V  |   |
| <b>SMALL-SIGNAL CHARACTERISTICS</b>   |   |               |  |   |  |  |   |
| Current - Gain - Bandwidth Product<br>( $I_C = 10\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ , $f = 100\text{ MHz}$ )   | BC546<br>BC547<br>BC548   | $f_T$         | 150<br>150<br>150  | 300<br>300<br>300   | -<br>-<br>-  | MHz  |   |
| Output Capacitance<br>( $V_{CB} = 10\text{ V}$ , $I_C = 0$ , $f = 1.0\text{ MHz}$ )   |   | $C_{obo}$     | -  | 1.7   | 4.5  | pF   |   |
| Input Capacitance<br>( $V_{EB} = 0.5\text{ V}$ , $I_C = 0$ , $f = 1.0\text{ MHz}$ )   |   | $C_{ibo}$     | -  | 10  | -  | pF   |   |
| Small - Signal Current Gain<br>( $I_C = 2.0\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ , $f = 1.0\text{ kHz}$ )   | BC546<br>BC547/548<br>BC547A<br>BC546B/547B/548B<br>BC547C/548C   | $h_{fe}$      | 125<br>125<br>125<br>240<br>450  | -<br>-<br>220<br>330<br>600   | 500<br>900<br>260<br>500<br>900  | -  |   |
| Noise Figure<br>( $I_C = 0.2\text{ mA}$ , $V_{CE} = 5.0\text{ V}$ , $R_S = 2\text{ k}\Omega$ ,<br>$f = 1.0\text{ kHz}$ , $\Delta f = 200\text{ Hz}$ )   | BC546<br>BC547<br>BC548   | NF            | -<br>-<br>-  | 2.0<br>2.0<br>2.0   | 10<br>10<br>10   | dB   |   |

1.  $I_B$  is value for which  $I_C = 11\text{ mA}$  at  $V_{CE} = 1.0\text{ V}$ .

# BC546B, BC547A, B, C, BC548B, C

## BC547/BC548




Figure 1. Normalized DC Current Gain




Figure 2. "Saturation" and "On" Voltages




Figure 3. Collector Saturation Region




Figure 4. Base-Emitter Temperature Coefficient




Figure 5. Capacitances




Figure 6. Current-Gain - Bandwidth Product

BC546




Figure 7. DC Current Gain




Figure 8. "On" Voltage




Figure 9. Collector Saturation Region




Figure 10. Base-Emitter Temperature Coefficient




Figure 11. Capacitance




Figure 12. Current-Gain - Bandwidth Product

## BC546B, BC547A, B, C, BC548B, C

### DEVICE ORDERING INFORMATION



| Device     | Package            | Shipping†          |
|------------|--------------------|--------------------|
| BC546B     | TO-92              | 5000 Units / Bulk  |
| BC546BG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC546BRL1  | TO-92              | 2000 / Tape & Reel |
| BC546BRL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC546BZL1  | TO-92              | 2000 / Ammo Box    |
| BC546BZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC547ARL   | TO-92              | 2000 / Tape & Reel |
| BC547ARLG  | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC547ARL1  | TO-92              | 2000 / Tape & Reel |
| BC547ARL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC547AZL1  | TO-92              | 2000 / Ammo Box    |
| BC547AZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC547B     | TO-92              | 5000 Units / Bulk  |
| BC547BG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC547BRL1  | TO-92              | 2000 / Tape & Reel |
| BC547BRL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC547BZL1  | TO-92              | 2000 / Ammo Box    |
| BC547BZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC547C     | TO-92              | 5000 Units / Bulk  |
| BC547CG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC547CZL1  | TO-92              | 2000 / Ammo Box    |
| BC547CZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC548B     | TO-92              | 5000 Units / Bulk  |
| BC548BG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC548BRL1  | TO-92              | 2000 / Tape & Reel |
| BC548BRL1G | TO-92<br>(Pb-Free) | 2000 / Tape & Reel |
| BC548BZL1  | TO-92              | 2000 / Ammo Box    |
| BC548BZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |
| BC548C     | TO-92              | 5000 Units / Bulk  |
| BC548CG    | TO-92<br>(Pb-Free) | 5000 Units / Bulk  |
| BC548CZL1  | TO-92              | 2000 / Ammo Box    |
| BC548CZL1G | TO-92<br>(Pb-Free) | 2000 / Ammo Box    |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# BC546B, BC547A, B, C, BC548B, C

## PACKAGE DIMENSIONS

TO-92 (TO-226)  
CASE 29-11  
ISSUE AL



### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.175  | 0.205 | 4.45        | 5.20  |
| B   | 0.170  | 0.210 | 4.32        | 5.33  |
| C   | 0.125  | 0.165 | 3.18        | 4.19  |
| D   | 0.016  | 0.021 | 0.407       | 0.533 |
| G   | 0.045  | 0.055 | 1.15        | 1.39  |
| H   | 0.095  | 0.105 | 2.42        | 2.66  |
| J   | 0.015  | 0.020 | 0.39        | 0.50  |
| K   | 0.500  | ---   | 12.70       | ---   |
| L   | 0.250  | ---   | 6.35        | ---   |
| N   | 0.080  | 0.105 | 2.04        | 2.66  |
| P   | ---    | 0.100 | ---         | 2.54  |
| R   | 0.115  | ---   | 2.93        | ---   |
| V   | 0.135  | ---   | 3.43        | ---   |

### STYLE 17:

1. COLLECTOR
2. BASE
3. EMITTER

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85062-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.