

# Bipolar Transistor

(-)-50 V, (-)1 A, Low  $V_{CE(sat)}$ ,  
(PNP)NPN Single CPH3

## CPH3116, CPH3216

### Features

- Adoption of MBIT Processes
- Large Current Capacity
- Low Collector-to-emitter Saturation Voltage
- High-speed Switching
- Ultrasmall Package Facilitates Miniaturization in End Products  
(Mounting Height : 0.9 mm)
- High Allowable Power Dissipation
- These are Pb-Free Devices

### Applications

- Relay Drivers, Lamp Drivers, Motor Drivers, Flash


### Specifications

( ): CPH3116

### ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	$V_{CBO}$		(-50)80	V
Collector-to-Emitter Voltage	$V_{CES}$		(-50)80	V
Emitter-to-Base Voltage	$V_{CEO}$		(-50)	V
	$V_{EBO}$		(-5)	V
Collector Current	$I_C$		(-)1.0	A
Collector Current (Pulse)	$I_{CP}$		(-)3	A
Base Current	$I_B$		(-)200	mA
Collector Dissipation	$P_C$	When mounted on ceramic substrate (600 mm <sup>2</sup> × 0.8 mm)	0.9	W
Junction Temperature	$T_j$		150	°C
Storage Temperature	$T_{stg}$		-55 to +150	°C


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.




1: Base  
2: Emitter  
3: Collector

CPH3  
CASE 318BA

### MARKING DIAGRAMS



### ELECTRICAL CONNECTION



CPH3116

CPH3216

### ORDERING INFORMATION

Device	Package	Shipping <sup>†</sup>
CPH3116-TL-E	CPH3 (Pb-Free)	3000 / Tape & Reel
CPH3216-TL-E	CPH3 (Pb-Free)	3000 / Tape & Reel


<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#).

# CPH3116, CPH3216

## ELECTRICAL CHARACTERISTICS (Ta = 25°C)

Parameter	Symbol	Conditions	Ratings			Unit
			Min	Typ	Max	
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = (-)40\text{ V}, I_E = 0\text{ A}$	-	-	(-)0.1	$\mu\text{A}$
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = (-)4\text{ V}, I_C = 0\text{ A}$	-	-	(-)0.1	$\mu\text{A}$
DC Current Gain	$h_{FE}$	$V_{CE} = (-)2\text{ V}, I_C = (-)100\text{ mA}$	200	-	560	
Gain-Bandwidth Product	$f_T$	$V_{CE} = (-)10\text{ V}, I_C = (-)300\text{ mA}$	-	420	-	MHz
Output Capacitance	$C_{ob}$	$V_{CB} = (-)10\text{ V}, f = 1\text{ MHz}$	-	(9)6	-	pF
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)1}$	$I_C = (-)500\text{ mA}, I_B = (-)10\text{ mA}$	-	(-280)130	(-430)190	mV
	$V_{CE(sat)2}$	$I_C = (-)300\text{ mA}, I_B = (-)6\text{ mA}$	-	(-145)90	(-220)135	mV
Base-to-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)500\text{ mA}, I_B = (-)10\text{ mA}$		(-)0.81	(-)1.2	V
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10\text{ }\mu\text{A}, I_E = 0\text{ A}$	(-50)80	-	-	V
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CES}$	$I_C = (-)100\text{ }\mu\text{A}, R_{BE} = 0\text{ }\Omega$	(-50)80	-	-	V
	$V_{(BR)CEO}$	$I_C = (-)1\text{ mA}, R_{BE} = \infty$	(-)50	-	-	V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10\text{ }\mu\text{A}, I_C = 0\text{ A}$	(-)5	-	-	V
Turn-On Time	$t_{on}$	See specified Test Circuit	-	35	-	ns
Storage Time	$t_{stg}$		-	(170)330	-	ns
Fall Time	$t_f$		-	(30)40	-	ns


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.




$I_C = 20I_{B1} = -20I_{B2} = 500\text{ mA}$   
 (For PNP, the polarity is reversed.)

**Figure 1. Switching Time Test Circuit**


# CPH3116, CPH3216




**Figure 2.  $I_C - V_{CE}$**




**Figure 3.  $I_C - V_{CE}$**




**Figure 4.  $I_C - V_{BE}$**



**Figure 5.  $I_C - V_{BE}$**



**Figure 6.  $h_{FE} - I_C$**



**Figure 7.  $h_{FE} - I_C$**

# CPH3116, CPH3216




Figure 8.  $f_T - I_C$




Figure 9.  $f_T - I_C$




Figure 10.  $C_{ob} - V_{CB}$




Figure 11.  $C_{ob} - V_{CB}$




Figure 12.  $V_{CE(sat)} - I_C$




Figure 13.  $V_{CE(sat)} - I_C$

# CPH3116, CPH3216




Figure 14.  $V_{CE(sat)} - I_C$




Figure 15.  $V_{CE(sat)} - I_C$




Figure 16.  $V_{BE(sat)} - I_C$




Figure 17.  $V_{BE(sat)} - I_C$




Figure 18. ASO





Figure 19.  $P_C - T_a$

**MECHANICAL CASE OUTLINE**  
**PACKAGE DIMENSIONS**

**CPH3**  
**CASE 318BA**  
**ISSUE O**

DATE 30 NOV 2011



<b>DOCUMENT NUMBER:</b>	<b>98AON65437E</b>	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
<b>DESCRIPTION:</b>	<b>CPH3</b>	<b>PAGE 1 OF 1</b>

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

