



Viewed On Component Side



## TECHNICAL DATA :

- Core : Toriod  $\emptyset$  14 /  $\emptyset$  9 / H 5  $\mu$ i 6000 Ferrite Material
- Wire :  $\emptyset$ 0.28 Grade 1 Class F
- Rated Current Per Winding : 1A referred to 250V-50Hz and + 60°C ambient temperature
- Rated Inductance Per Winding : 6.8mH -30% + 50% at 10KHz , 0.1mA
- Rated DC Resistance Per Winding (Typical) : 305m $\Omega$
- Test Voltage Between Windings : 1500VAC - 50 Hz
- Climatic Category : DIN GKC (-40 to +125°C; humidity cat. C)
- Material Case : PBT at 30% Fibreglass UL94V0
- Packaging Unit : 1444 pieces

RoHS compliance  
Please, refer to general catalog for unspecified parameters.

a	
IND	DATE

## Radiohm Specification

Designation : 42V20 1000



Part number : \_\_\_\_\_  
Preliminary :  Final :

Date : 17/05/2005

## Customer Specification Approval

Part number : \_\_\_\_\_

Signature : \_\_\_\_\_ Name : \_\_\_\_\_ Title : \_\_\_\_\_ Date : \_\_\_\_\_