

PC900V/PC900VQ

* Lead forming type (I type) and taping reel type (P type) are also available. (PC900VI/PC900VP)

** TÜV (DIN-VDE0884) approved type is also available as an option.

■ Features

1. High reliability type (PC900VQ)
2. Normal OFF operation, open collector output
3. TTL and LSTTL compatible output
4. Operating supply voltage V_{CC} : 3 to 15V
5. High isolation voltage between input and output (V_{iso} : 5 000V_{rms})
6. Recognized by UL, file No. E64380


■ Applications

1. Isolation between logic circuits
2. Logic level shifters
3. Line receivers
4. Replacements for relays and pulse transformers
5. Noise reduction

Digital Output Type OPIC Photocoupler

■ Outline Dimensions

(Unit : mm)



* "OPIC" (Optical IC) is a trademark of the SHARP Corporation.
An OPIC consists of a light-detecting element and signal-processing circuit integrated onto a single chip.

■ Absolute Maximum Ratings

(Ta = 25°C)

	Parameter	Symbol	Rating	Unit
Input	Forward current	I _F	50	mA
	[*] Peak forward current	I _{FM}	1	A
	Reverse voltage	V _R	6	V
	Power dissipation	P	70	mW
Output	Supply voltage	V _{CC}	16	V
	High level output voltage	V _{OH}	16	V
	Low level output current	I _{OL}	50	mA
	Power dissipation	P _O	150	mW
	Total power dissipation	P _{tot}	170	mW
	[*] Isolation voltage	V _{iso}	5 000	V _{rms}
	Operating temperature	T _{opr}	- 25 to + 85	°C
	Storage temperature	T _{stg}	- 40 to + 125	°C
	[*] Soldering temperature	T _{sol}	260	°C

*1 Pulse width <= 100μs, Duty ratio : 0.001

*2 40 to 60% RH, AC for 1 minute

*3 For 10 seconds

■ Electro-optical Characteristics

(Ta = 0 to + 70°C unless specified)

Parameter		Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Input	Forward voltage	V _F	I _F = 4mA	-	1.1	1.4	V
			I _F = 0.3mA	0.7	1.0	-	
	Reverse current	I _R	Ta = 25°C, V _R = 3V	-	-	10	μA
Output	Terminal capacitance	C _t	Ta = 25°C, V = 0, f = 1kHz	-	30	250	pF
	Operating supply voltage	V _{CC}		3	-	15	V
	Low level output voltage	V _{OL}	I _{OL} = 16mA, V _{CC} = 5V, I _F = 4mA	-	0.2	0.4	V
	High level output current	I _{OH}	V _O = V _{CC} = 15V, I _F = 0	-	-	100	μA
	Low level supply current	I _{CCL}	V _{CC} = 5V, I _F = 4mA	-	2.5	5.0	mA
Transfer characteristics	High level supply current	I _{CCH}	V _{CC} = 5V, I _F = 0	-	1.0	5.0	mA
	*4 "High→Low" threshold input current	I _{FHL}	Ta = 25°C, V _{CC} = 5V, R _L = 280Ω	-	1.1	2.0	mA
			V _{CC} = 5V, R _L = 280Ω	-	-	4.0	
	*5 "Low→High" threshold input current	I _{FLH}	Ta = 25°C, V _{CC} = 5V, R _L = 280Ω	0.4	0.8	-	mA
			V _{CC} = 5V, R _L = 280Ω	0.3	-	-	
	*6 Hysteresis	I _{FLH} / I _{FHL}	V _{CC} = 5V, R _L = 280Ω	0.5	0.7	0.9	-
*7 Response time	Isolation resistance	R _{ISO}	Ta = 25°C, DC500V, 40 to 60% RH	5 x 10 ¹⁰	10 ¹¹	-	Ω
	"High→Low" propagation delay time	t _{PHL}	Ta = 25°C V _{CC} = 5V, I _F = 4mA R _L = 280Ω	-	1	3	μs
	"Low→High" propagation delay time	t _{PLH}		-	2	6	
	Fall time	t _f		-	0.05	0.5	
	Rise time	t _r		-	0.1	0.5	

*4 I_{FHL} represents forward current when output goes from high to low.*5 I_{FLH} represents forward current when output goes from low to high.*6 Hysteresis stands for I_{FLH} / I_{FHL}.

*7 Test circuit for response time is shown below.

<Precautions for Use>

Connect a capacitor of more than 0.1 μF between V_{CC} and GND.

Test Circuit for Response Time





Fig. 1 Forward Current vs. Ambient Temperature




Fig. 3 Forward Current vs. Forward Voltage




Fig. 5 Relative Threshold Input Current vs. Ambient Temperature




Fig. 2 Power Dissipation vs. Ambient Temperature




Fig. 4 Relative Threshold Input Current vs. Supply Voltage




Fig. 6 Low Level Output Voltage vs. Low Level Output Current




Fig. 7 Low Level Output Voltage vs. Ambient Temperature




Fig. 8 Supply Current vs. Supply Voltage




Fig. 9 Propagation Delay Time vs. Forward Current





Fig.10 Rise Time, Fall Time vs. Load Resistance



■ Precautions for Use

- (1) It is recommended that a by-pass capacitor of more than $0.01\mu F$ is added between V_{CC} and GND near the device in order to stabilize power supply line.
- (2) Handle this product the same as with other integrated circuits against static electricity.
 - Please refrain from soldering under preheating and refrain from soldering by reflow.
 - Please refer to the chapter "Precautions for Use."