

Current Chokes, Axial Leads, Noise Suppression Applications




FEATURES

- These inductors have copper winding on a bobbin with axial terminals
- Protection by a thermo sleeve
- Cylindrical shape allows use in automatic cabling machines use
- This inductor series is specially designed for power supply filtering
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

DIMENSIONS in millimeters



ELECTRICAL SPECIFICATIONS

Inductance range	1 μ H to 18 000 μ H
Tolerance	$\pm 20\%$
Maximum voltage	500 V _{RMS}
Measuring conditions	U = 100 mV _{RMS}

MECHANICAL SPECIFICATIONS

Coating	Thermo sleeve
Weight	4 g

PACKAGING

500 pieces tape and reel

ENVIRONMENTAL SPECIFICATIONS

Operating temperature range	0 °C to +70 °C
Temperature limits	-55 °C to +125 °C

MARKING

 Print marked:
 manufacturer, series and style, inductance value, date code

ORDERING INFORMATION

IG	70	3900 μH	$\pm 20\%$	R	e1
MODEL	STYLE	INDUCTANCE VALUE	TOLERANCE	PACKAGING	LEAD FINISH e1: SnAgCu

SAP PART NUMBERING GUIDELINES

I	G	7	0	3	9	2	M	R	1	0						
MODEL		STYLE		INDUCTANCE VALUE			TOL.	PACKAGING CODE			SPECIAL (IF APPLICABLE)					

See the end of this data book for conversion tables



STANDARD VALUES - IG70 INDUCTORS				
INDUCTANCE VALUE μH I_{DC} = 0 A	TOLERANCE %	TEST FREQUENCY	DCR MAX. Ω	I MAX. A
1	± 20 %	1 kHz	0.009	5.3
1.2	± 20 %	1 kHz	0.010	5
1.5	± 20 %	1 kHz	0.011	4.8
1.8	± 20 %	1 kHz	0.012	4.6
2.2	± 20 %	1 kHz	0.013	4.4
2.7	± 20 %	1 kHz	0.014	4.2
3.3	± 20 %	1 kHz	0.016	4
3.9	± 20 %	1 kHz	0.017	3.8
4.7	± 20 %	1 kHz	0.022	3.4
5.6	± 20 %	1 kHz	0.024	3.2
6.8	± 20 %	1 kHz	0.026	3.1
8.2	± 20 %	1 kHz	0.028	3
10	± 20 %	1 kHz	0.033	2.8
12	± 20 %	1 kHz	0.037	2.6
15	± 20 %	1 kHz	0.040	2.5
18	± 20 %	1 kHz	0.044	2.4
22	± 20 %	1 kHz	0.060	2.2
27	± 20 %	1 kHz	0.070	1.9
33	± 20 %	1 kHz	0.075	1.8
39	± 20 %	1 kHz	0.084	1.7
47	± 20 %	1 kHz	0.104	1.6
56	± 20 %	1 kHz	0.130	1.4
68	± 20 %	1 kHz	0.145	1.3
82	± 20 %	1 kHz	0.152	1.3
100	± 20 %	1 kHz	0.208	1.1
120	± 20 %	1 kHz	0.283	0.94
150	± 20 %	1 kHz	0.330	0.87
180	± 20 %	1 kHz	0.362	0.83
220	± 20 %	1 kHz	0.505	0.70
270	± 20 %	1 kHz	0.557	0.67
330	± 20 %	1 kHz	0.650	0.62
390	± 20 %	1 kHz	0.770	0.57
470	± 20 %	1 kHz	1.03	0.49
560	± 20 %	1 kHz	1.14	0.47
680	± 20 %	1 kHz	1.50	0.41
820	± 20 %	1 kHz	1.98	0.36
1000	± 20 %	1 kHz	2.3	0.33
1200	± 20 %	1 kHz	2.55	0.31
1500	± 20 %	1 kHz	3	0.29
1800	± 20 %	1 kHz	4	0.25
2200	± 20 %	1 kHz	4.40	0.24
2700	± 20 %	1 kHz	5.80	0.21
3300	± 20 %	1 kHz	6.56	0.2
3900	± 20 %	1 kHz	8.63	0.17
4700	± 20 %	1 kHz	10.1	0.16
5600	± 20 %	1 kHz	11.2	0.15
6800	± 20 %	1 kHz	15	0.13
8200	± 20 %	1 kHz	20.8	0.11
10 000	± 20 %	1 kHz	23.4	0.1
12 000	± 20 %	1 kHz	26	0.1
15 000	± 20 %	1 kHz	36	0.08
18 000	± 20 %	1 kHz	40	0.08



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.